

115-125 (T3)

NEW

D-MAX



McCORMICK

		D-115 MAX	D-125 MAX
ENGINE			
FPT TIER 3A		NEF 4 -2V	NEF 4 -2V
MAX. POWER (ISO)	HP/KW	112/82,5	120/88
RATED SPEED	RPM	2200	2200
MAX. TORQUE	LB. (NM)	374 (510)	378 (515)
MAX. TORQUE SPEED	RPM	1250	1250
BORE/STROKE	IN. (MM)	4.1 / 5.2 (104/132)	4.1 / 5.2 (104/132)
DISPLACEMENT / CYLINDERS	CM ³	273 (4485) /4	273 (4485) /4
WATER COOLING		●	●
DRY AIR FILTER		●	●
FUEL TANK CAPACITY	GAL. (LT)	48 (180)	48 (180)
CLUTCH			
INDEPENDENT DRY SINGLE-PLATE CLUTCH	IN. (MM)	13"(330)	13"(330)
MECHANICALLY OPERATED		●	●
MULTY-DISC WET CLUTCH		○	○
DE-CLUTCH CONTROL: BOTTON OPERATED CLUTCH		○	○
TRANSMISSION			
MECH. REV. SHUTTLE+SPEED FOUR: 12FWD + 12REV 25 MPH (40KM/H)		●	●
MECH. REV. SHUTTLE+SPEED FOUR+CREEPER: 16FWD+16REV 25 MPH (40KM/H)		○	○
HYDR. REV. SHUTTLE+SPEED FOUR+T-TRONIC: 36FWD+12REV 25 MPH (40KM/H)		○	○
HYDR. REV. SHUTTLE+SPEED FOUR+T-TRONIC+CREEPER: 48FWD+16REV 25 MPH (40KM/H)		○	○
SHUTTLE MODULATION CONTROL: POTENTIOMETER FOR ADJUSTMENT OF POWER SHUTTLE RESPONSE		○	○
POWER TAKE-OFF			
WET MULTI-DISC		●	●
ELECTROHYDRAULIC CONTROL		●	●
2 SPEEDS 540/1000 RPM		●	●
2 SPEEDS 540/540E RPM		○	○
1"3/8 (34.9 MM) PTO SHAFT WITH 6 SPLINES		●	●
1"3/8 (34.9 MM) PTO SHAFT WITH 21 SPLINES		○	○
GROUND SPEED PTO		○	○
4WD FRONT AXLE			
ELECTROHYDRAULIC 4WD ENGAGEMENT		●	●
MAX. STEERING ANGLE		55°	55°
TWIN-LOCK ELECTROHYDRAULIC DIFF-LOCKS		●	●
BRAKES			
ANNULAR PISTON REAR BRAKES		●	●
AUTOMATIC 4WD ENGAGEMENT ON BRAKING		●	●
HYDRAULIC POWER LIFT			
DRAFT, POSITION, INTERMIX AND FLOATING CONTROL FUNCTIONS		●	●
MECHANICALLY OPERATED		●	●
ELECTRONICALLY-OPERATED		○	○
LIFTING CAPACITY WITH TWO 2-INCH (50MM) ASSISTOR RAMS	LB. (KG)	9900 (4500)	9900 (4500)
MAX. OPERATING PRESSURE	BAR	180	180
TOTAL PUMP FLOW (HITCH + STEERING)	GPM (LT/MIN)	17.3 + 7.6 (66 + 29)	17.3 + 7.6 (66 + 29)
CLOSED CENTRE SYSTEM PUMP FLOW (HITCH + STEERING)	GPM (LT/MIN)	29 + 10 (110 + 38)	29 + 10 (110 + 38)
CAT 2 THREE -POINT LINKAGE		●	●
REMOTE VALVES STD/OPT		2/3	2/3

Key: ● standard ○ option — not available

		D-115 MAX	D-125 MAX
CAB AND DRIVING SEAT			
MECHANICALLY SUSPENDED SEAT		●	●
SUSPENDED PLATFORM		●	●
REAR FOLDING ROPS		●	●
RIGID SUNROOF		○	○
DELUXE CAB / RADIO ADAPTOR		○	○
HEATING / VENTILATION		○	○
AIR-CONDITIONING		○	○
DIMENSIONS AND WEIGHTS (IN RUNNING ORDER)			
FRONT TYRES		14.9 R24	14.9 R24
REAR TYRES		16.9 R38	16.9 R38
A - LENGTH (WITH BALLAST)	IN. (MM)	187 (4755)	187 (4755)
B - WHEELBASE 4WD	IN. (MM)	100 (2540)	100 (2540)
C - GROUND CLEARANCE 4WD	IN. (MM)	14.5 (370)	14.5 (370)
D - HEIGHT TO ROPS	IN. (MM)	109.5 (2780)	109.5 (2780)
D - HEIGHT TO CAB	IN. (MM)	109 (2770)	109 (2770)
E - MIN. WIDTH	IN. (MM)	82 (2092)	82 (2092)
WEIGHT (WITHOUT BALLAST) 4WD + CAB	LB. (KG)	9240 (4200)	9240 (4200)
OPTIONAL EQUIPMENT			
6 - 8 - 10 FRONT WEIGHTS		○	○
2 - 4 REAR WEIGHTS		○	○

Key: ● standard ○ option — not available

